



- Full bucket indicator avoids overflows
- Simple manual operation, and unit will run continuously if you press the “Minus” button until “CO” flash for 5 seconds and then display
- Single fan speed (25 Pints) & double fan speed (35 & 50 Pints)
- Low-temperature operation (38°F)



Low Noise Airflow System

High performance centrifugal fan ensures quiet operation as low as 47db(A)



Energy Efficient

Energy Star means its more energy efficient and helps reduce your utility bill



Filter Monitor

Washable filter helps to reduce bacteria, odors, and particles



Warranty

2-Year Exchange

Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense Dehumidifiers quietly collect water into the slide-out internal bucket, or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Easy control and the very low sound level make this a versatile choice. Additional features include an adjustable humidistat, easy accessible and washable filter, and full-tank alert.

Note:
New DOE test procedure, equivalent to previous 30 Pints:



TECHNICAL SPECIFICATIONS

Performance

Model #	DH3020K1W	DH3521K1W	DH5021KP1W	DH70K1SFRE20
Dehumidification(Pints/24 hours)	25*	35	50	50
Coverage	Up to 700 sq. ft.	Up to 1,000 sq.ft.	Up to 1,500 sq. ft.	Up to 1,500 sq. ft.
Refrigerant	R410a	R410a	R410a	R410a
Noise Level in dB(A) (Low-High)	47 dB(A)	47-49 dB(A)	48-50 dB(A)	47-49 dB(A)

Electrical

Voltage / Freq / Amps	1Ph\115V\60Hz	1Ph\115V\60Hz	1Ph\115V\60Hz	1Ph\115V\60Hz

General Features

Unit Control Type	Electronic	Electronic	Electronic	Electronic
Display Type	LED	LED	LED	LED
Continuous Run	Yes	Yes	Yes	Yes
Timer Clock	No	Yes	Yes	Yes
Number of Fan Speeds	1	2	2	2
Water Pump	No	No	Yes	No

Refrigeration Compartment

Auto Bucket Shutoff	Yes	Yes	Yes	Yes
Bucket Capacity	8.5 pints	11.4 pints	16.7 pints	16.7 pints
Bucket Shutoff Capacity	7.0 pints	9.1 pints	13.3 pints	13.3 pints
Garden Hose Connection	Standard Garden Hose (not included)			
Filter Monitor/Type	Yes/Framed Woven	Yes/Framed Woven	Yes/Framed Woven	Yes/Framed Woven

Approvals

Safety	UL	UL	UL	UL
Energy	Energy Star	Energy Star	Energy Star	Energy Star

Shipping

Unit Dimension WxDxH (inch)	13.2 x 8.6 x 19.9	14.0 x 10.75 x 20	15.25 x 11.8 x 24.7	15.25 x 11.8 x 24.7
Carton Dimension WxDxH (inch)	15.0 x 10.5 x 21.1	15.9 x 13.2 x 21.0	16.9 x 13.0 x 26.3	16.9 x 13.0 x 26.3
Net Weight /Gross Weight (lbs)	28.2 / 30.8	34.1 / 38.3	42.3 / 46.6	42.3 / 46.6

Warranty/UPC

Warranty (Exchange)	2 Years	2 Years	2 Years	2 Years
UPC	819130026824	819130027357	819130028248	819130029153

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2022 Hisense Canada Co., Ltd. All rights reserved.

Note:
New DOE test procedure, equivalent to previous 30 Pints:

