

# Hisense

70  
PINT

DEHUMIDIFIER WITH BUILT IN PUMP

up to 1500sq. ft. coverage

## Model: DH-70KP1SFRE00

Dehumidifier with built-in pump



- Built-in Pump, quick-connect hose included
- 3 Modes - Auto, Continuous, Manual
- 3 Fan Speeds (High, Low, Auto)
- Filter indicator-Washable filter to help reduce bacteria, odours and particles



### Low Noise Airflow System

High-performance centrifugal fan ensures quiet operation, achieving just 46 dB(A) with the fan set on "Low"



### Energy Efficient

Energy Star® means its more energy efficient and helps reduce your utility bill



### Warranty

2 Years Parts & Labour

## Built-in Pump - Helps keep your home conveniently dry, fresh, and quiet

This Hisense 70-Pint 2-Speed Dehumidifier has a built-in pump that can quietly remove water out a basement window or into a sink using the included quick-connect hose. This reliable and eco-friendly, Energy Star® certified dehumidifier can operate at temperatures as low as 3 degrees Celsius. Three operating modes (manual set, continuous and auto dry) and the low\* noise level make this a versatile choice. During dehumidification, water accumulates in the internal water tank or is continuously pumped out using the included quick-connect hose. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

TECHNICAL SPECIFICATIONS	
<b>Performance</b>	
Hisense-Model	DH-70KP1SFRE00
Dehumidification (Pints/24 hrs)	70
Coverage	up to 1500 sq. ft
Refrigerant	R-410A
Noise Level in dB(A)	46 - 48 dB(A)
<b>Electrical</b>	
Voltage / Freq / Amps	115V/60Hz / 6.8A
<b>Control Features</b>	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Fan Speeds	3 speeds (Low, High, Auto)
Timer-Clock	Yes
Pump mode	Yes
<b>General Features</b>	
Auto Bucket Shutoff	Yes
Bucket Capacity	13.7 pints
Bucket Shutoff Capacity	11.0 pints
Garden Hose Connection	Yes- garden hose not included
Washable Filters	Yes
Max. Pump Discharge Height	192 inches (4.88 metres)
<b>Accessories</b>	
Quick Connect Hose	Yes, included (9mm diameter)
<b>Approvals</b>	
Safety	ETL
Energy	CEC

<b>Shipping</b>	
Unit Dimension WxDxH (mm)	387 x 300 x 628
Carton Dimension WxDXH (mm)	435 x 335 x 667
Net Weight /Gross Weight (Kg)	21.3/ 23.0
Unit Dimension WxDxH (inch)	15.3 x 11.8 x 24.7
Carton Dimension WxDXH (inch)	17.1 x 13.3 x 26.3
Net Weight /Gross Weight (lbs)	46.8/ 50.7
<b>Warranty/UPC</b>	
Parts & Labour	2 years
UPC	857603006294



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2018 Hisense Canada, All rights reserved